



Reduções



com rosca BSP
56124/



sem rosca
56125/





Conectores Retos



unidut cônico
sem rosca BSP
56126/0



com rosca BSP
56127/0





Conectores Flexor



unidut cônico
sem rosca BSP
56126/0



com rosca BSP
56127/0



ACESSÓRIOS ELETRODUTOS

REF.	EMB.	789.1435.	BITOLA	DIMENSÃO [MM]		
				A	B	C

reduções com rosca

56124/001	48	01087 9	¾" x ½"	22	14	
56124/002	36	01088 6	1" x ½"	22	12	
56124/003	36	01089 3	1" x ¾"	22	12	
56124/004	36	01090 9	1.¼" x ½"	30	18	
56124/005	36	01091 6	1.¼" x ¾"	30	18	
56124/006	36	01092 3	1.½" x 1"	30	18	
56124/008	24	01093 0	1.½" x ¾"	31	18	
56124/009	24	01094 7	1.½" x 1"	31	18	
56124/010	24	01095 4	1.½" x 1.¼"	31	18	
56124/013	24	01096 1	2" x 1"	34	20	
56124/015	24	01097 8	2" x 1.½"	34	20	
56124/021	12	01098 5	2.½" x 2"	40	26	
56124/028	6	01099 2	3" x 2.½"	45	30	
56124/036	6	01100 5	4" x 3"	56	40	

reduções sem rosca [acompanham parafusos]

56125/001	24	01101 2	¾" x ½"	22	26	50
56125/002	24	01102 9	1" x ½"	22	32,5	50
56125/003	24	01103 6	1" x ¾"	28	32,5	55

conector reto sem rosca [acompanham parafusos]

56126/001	50	01107 4	½"	22	15	45
56126/002	50	01108 1	¾"	28	16	48
56126/003	20	01109 8	1"	34,5	16	52
56126/007	5	00660 5	2.½"	78	22	71
56126/008	5	00661 2	3"	90,5	24	80
56126/010	5	00662 9	4"	116,5	28	90

conector reto com rosca [acompanham parafusos e arruelas]

56127/001	100	00899 9	½"	22	15	45
56127/002	100	00900 2	¾"	28	16	48
56127/003	50	00901 9	1"	34,5	16	52
56127/007	5	00905 7	2.½"	78	22	71
56127/008	5	00906 4	3"	90,5	24	80
56127/010	5	00907 1	4"	116,5	28	90



conector flexor reto sem rosca [acompanham parafusos]

56126/021	50	04437 9	½"	22	10	35
56126/022	50	04438 6	¾"	28	10	35
56126/023	30	04439 3	1"	34,5	10	35
56126/024	20	05791 1	1.¼"	43	11	44
56126/025	10	05792 8	1.½"	49	11	44
56126/026	10	05793 5	2"	61	11	44

conector flexor reto com rosca [acompanham parafusos e arruelas]

56127/021	100	05140 7	½"	22	10	35
56127/022	100	05141 4	¾"	28	10	35
56127/023	50	05142 1	1"	34,5	10	35
56127/024	20	05785 0	1.¼"	43	11	44
56127/025	20	05786 7	1.½"	49	11	44
56127/026	10	05787 4	2"	61	11	44


Conectores Curvos



REF.	EMB.	789.1435.	BITOLA	DIM. MM		
				A	B	C
conector curvo com rosca [acompanham parafusos e arruelas]						
56128/001	50	00908 8	½"	22	26,5	15,5
56128/002	50	00909 5	¾"	27,5	26	15,5
56128/003	20	00910 1	1"	34,5	32	16
56128/004	20	02054 0	1.¼"	43	35	19
56128/005	10	02055 7	1.½"	51,5	40	20
56128/006	10	02056 4	2"	64,5	45	22
56128/007	5	02057 1	2.½"	78	78	28
56128/008	5	02058 8	3"	91	91	30
56128/010	5	02059 5	4"	117	70	35

conector curvo sem rosca [acompanham parafusos]						
56129/001	50	00917 0	½"	22	26,5	
56129/002	50	00918 7	¾"	27,5	26	
56129/003	20	00919 4	1"	34,5	32	
56129/004	20	02060 1	1.¼"	43	35	
56129/005	10	02061 8	1.½"	51,5	40	
56129/006	10	02062 5	2"	64,5	45	
56129/007	5	02063 2	2.½"	78	50	
56129/008	5	02064 9	3"	91	60	
56129/010	5	02065 6	4"	117	70	


Luvras de Emenda



luvas de emenda [acompanham parafusos]

56131/001	50	01104 3	½"	22	55
56131/002	25	01105 0	¾"	28	60
56131/003	20	01106 7	1"	34,5	66
56131/007	5	00654 4	2.½"	77	95
56131/008	5	00655 1	3"	90	110
56131/010	5	00656 8	4"	115,5	125

Luvras de Emenda Flexor



luvas de emenda flexor [acompanham parafusos]

56131/021	50	04440 9	½"	22	45
56131/022	50	04441 6	¾"	28	45
56131/023	25	04442 3	1"	34,5	45
56131/024	20	05788 1	1.¼"	43	58
56131/025	10	05789 8	1.½"	49	58
56131/026	10	05790 4	2"	61	58

Buchas


Fabricadas em **liga de alumínio e zinco [zamak]**, possuem rosca padrão BSP [tipo gás].



56134/



56134/1



REF.	EMB.	789.1435.	BITOLA	DIM. mm		
				A	B	C
buchas [alumínio]						
56134/001	200	01121 0	3/8"	22	7,5	13
56134/002	200	01122 7	½"	25,5	8,5	15,5
56134/003	200	01123 4	¾"	31	9	21
56134/004	200	01124 1	1"	38,5	10	27
56134/005	200	01125 8	1.¼"	48	11	33
56134/006	200	01126 5	1.½"	54,5	12,5	41
56134/007	100	01127 2	2"	66,5	13	53
56134/008	40	01128 9	2.½"	83,5	15,5	67
56134/009	40	01129 6	3"	97	16,5	78
56134/011	20	01130 2	4"	122	18	103
buchas [zamak]						
56134/022	200	01131 9	½"	25,5	8,5	15,5
56134/023	200	01132 6	¾"	31	9	21
56134/024	200	01133 3	1"	38,5	10	27
56134/025	200	01134 0	1.¼"	48	11	33
56134/026	200	01135 7	1.½"	54,5	12,5	41
56134/027	100	01136 4	2"	66,5	13	53
56134/028	40	01137 1	2.½"	83,5	15,5	67
56134/029	40	01138 8	3"	97	16,5	78
56134/031	20	01139 5	4"	122	18	103
embalagens [5 unidades]						
56134/102	20	40100 2	½"	25,5	8,5	15,5
56134/103	20	40101 1	¾"	31	9	21
56134/104	20	40102 8	1"	38,5	10	27

Arruelas


Fabricadas em **liga de alumínio e zinco [zamak]**, possuem rosca padrão BSP [tipo gás].



56135/



56135/1



arruela [alumínio]

56135/001	200	01140 1	3/8"	26	4
56135/002	200	01141 8	½"	26	4
56135/003	200	01142 5	¾"	32	4
56135/004	200	01143 2	1"	40	5
56135/005	200	01144 9	1.¼"	49	5
56135/006	200	01145 6	1.½"	55	5
56135/007	100	01146 3	2"	69	5,5
56135/008	40	01147 0	2.½"	83	6,5
56135/009	40	01148 7	3"	96	8,5
56135/011	20	01149 4	4"	124	9
arruela [zamak]					
56135/022	200	01150 0	½"	26	4
56135/023	200	01151 7	¾"	32	4
56135/024	200	01152 4	1"	40	5
56135/025	200	01153 1	1.¼"	49	5
56135/026	200	01154 8	1.½"	55	5
56135/027	100	01155 5	2"	69	5,5
56135/028	40	01156 2	2.½"	83	6,5
56135/029	40	01157 9	3"	96	8,5
56135/031	20	01158 6	4"	124	9
embalagens [5 unidades]					
56135/102	20	40103 5	½"	26	4
56135/103	20	40104 2	¾"	32	4
56135 /104	20	40105 9	1"	40	5

Abraçadeiras

Fabricadas em **aço carbono**, recebem acabamento **galvanizado eletrolítico**.


Tipo D



56136/0



56136/1




Tipo U



56137/0



56137/1




Tipo Chaveta



56137/0



56137/1



REF.	EMB.	789.1435.	BITOLA	DIM. mm		
				A	B	C
tipo D [fornecidas com parafuso e porca]						
56136/002	200	01159 3	½"	20	19	49,5
56136/003	200	01160 9	¾"	25,2	19	53
56136/004	200	01161 6	1"	31,5	19	62
56136/005	100	01162 3	1.¼"	40,5	27,5	71
56136/006	100	01163 0	1.½"	46,6	27,5	75
56136/007	100	01164 7	2"	58,4	27,5	92
56136/008	50	01165 4	2.½"	74,1	27,5	110,5
56136/009	50	01166 1	3"	86,8	27,5	130
56136/011	50	01167 8	4"	111,6	27,5	154
embalagens [3 unidades]						
56136/102	20	04040 1	½"	20	19	49,5
56136/103	20	04041 8	¾"	25,2	19	53
56136/104	20	04042 5	1"	31,5	19	62

tipo U

56137/002	200	01168 5	½"	20	19	51,5
56137/003	200	01169 2	¾"	25,2	19	60
56137/004	200	01170 8	1"	31,5	19	70
56137/005	100	01171 5	1.¼"	40,5	27,5	84
56137/006	100	01172 2	1.½"	46,6	27,5	94
56137/007	100	01173 9	2"	58,4	27,5	98
56137/008	50	01174 6	2.½"	74,1	27,5	125
56137/009	50	01175 3	3"	86,8	27,5	140
56137/011	50	01176 0	4"	111,6	27,5	158
embalagens [3 unidades]						
56137/102	20	04043 2	½"	20	19	51,5
56137/103	20	04044 9	¾"	25,2	19	60
56137/104	20	04045 6	1"	31,5	19	70

tipo chaveta

56138/002	200	01177 7	½"	20	27,5	39
56138/003	200	01178 4	¾"	25,2	27,5	42
56138/004	200	01179 1	1"	31,5	27,5	55
56138/005	100	01180 7	1.¼"	40,5	27,5	61
56138/006	100	01181 4	1.½"	46,6	27,5	68
56138/007	100	01182 1	2"	58,4	27,5	80
56138/008	50	01183 8	2.½"	74,1	27,5	96
56138/009	50	01184 5	3"	86,8	27,5	115
56138/011	50	01954 4	4"	111,6	27,5	136
embalagens [3 unidades]						
56138/102	20	04046 3	½"	20	27,5	39
56138/103	20	04047 0	¾"	25,2	27,5	42
56138/104	20	04048 7	1"	31,5	27,5	55

Indicado para todos os tipos de eletrodutos de aço-carbono conforme norma NBR 5624